

Electromagnetic Display Modules

H700 electromagnetic display modules with 10 to 58 cm characters height. Exceptional readability and reliability. Indoor or outdoor




www.bodet.com

Display with card


The main advantages are the following :

- Perfect readability even in harsh conditions such as bright light or direct sunlight (unlike diodes display systems)
- Operating temperature: from -40°C to +70°C
- No power consumption at rest
- Life over 70 million operations



Impulses diagram

Coil electrical diagram



Application Sectors

- Petrol price signs
- Time, temperature, date, sound display
- Sport timing and scoring
- Toll indications boards for highways and tunnel bridges
- Industrial productivity and quality measures
- Weight, speed, flow display...
- Queueing system, stock exchange, exchange rate
- Motel room prices
- Events count up and down in days, hours and seconds



Part No.	Outside dimensions without card HxWxD [mm]	Outside dimensions with card HxWxD [mm]	Character Size [mm]
H 710	148x95x51 mm	148x95x62 mm	105 mm
H 715	204x141x53 mm	204x141x65 mm	158 mm
H 725	306x230x53 mm	306x230x65 mm	253 mm
H 725E	306x230x51 mm	306x230x62 mm	253 mm
H 730	395x275x74 mm	395x275x90 mm	304 mm
H 745	575x400x67 mm	575x400x82 mm	456 mm
H 758	710x515x72 mm	710x515x87 mm	585 mm

Part No.	Maximum viewing distance	Casing
H 710	40 m	plastic/polycarbonate
H 715	60 m	plastic/polycarbonate
H 725	100 m	plastic/polycarbonate
H 725E	100 m	plastic/polycarbonate
H 730	125 m	aluminium
H 745	200 m	aluminium
H 758	250 m	aluminium

Part No.	Ord. No.
o H 710 WHITE	1628
o H 710 YELLOW	1631
o H 710 YELLOW w. CARD	49888
o H 715 YELLOW	1632
o H 715 YELLOW w. CARD	48523
o H 725E WHITE	43612
o H 725E YELLOW	48763
o H 725E YELLOW w. CARD	50841
o H 730 WHITE w.CARD	1630
o H 730 YELLOW	1629
o H 730 YELLOW w. CARD	46971
o H 745 WHITE w. CARD	50646
o H 745 YELLOW w. CARD	49889
o H 758 YELLOW w. CARD	49890

online ordering



electroniconline

www.soselectronic.com

Optoelectronics

