

Cables for TV, SAT and PC (continued)

RG Series

RG 58 - Coaxial data cable 50 Ohm, D=4,95mm, capacity 100pF/m PE isolation.

RG 174 - Coaxial data cable 50 Ohm, D=2,8mm, capacity 101pF/m PE isolation.



Part No.	Description
RG 174 A/U BK 100m	Coaxial cable 50 Ohm D=2,80mm black
RG 58 C/U BK 100m	Coaxial cable 50 Ohm D=4,95mm black

Part No.	Ord.No.
S RG 174 A/U BK 100m	55219
S RG 58 C/U BK 100m	31463

CAT5, CAT6 Series

Network cables for ETHERNET, LAN... 4x twisted pair with shielding, SSTP - shielding foil + copper braid. 100m reel.



Suitable tools - see chapter K

Part No.	Description
FTP CAT5e	Cable FTP 4xTwistedPair-solid wire CAT5e AWG24/1
FTP CAT5e PATCH	Cable FTP 4xTwistedPair-wire strand, AWG26/7
SSTP CAT6 PIMF LSOH	Cable 4xTwistedPair-solid wire AWG23/1 grey

Part No.	Ord.No.
S FTP CAT5e 100m	1459
S FTP CAT5e PATCH 100m	51694
S SSTP CAT6 PIMF LSOH 100m	69910

Network cables for ETHERNET, LAN, 4x twisted pair without shielding, 100m reel



Part No.	Description
CAT5 SOLID UTP	Cable 4xTwistedPair AWG24/1 Grey
CAT5 SOLID UTP CCA	Cable 4xTwistedPair AWG24/1 Grey
CAT5 SOLID UTP LSOH	Cable 4xTwistedPair AWG24/1 Grey

Part No.	Ord.No.
O CAT5 SOLID UTP 100m	76374
O CAT5 SOLID UTP CCA 100m	76375
O CAT5 SOLID UTP LSOH 100m	62363

USB Series



Part No.	Description
U2Z100 100m	USB Cable, Pair AWG28 (data)+2xAWG24 (power) D=4,7mm

Part No.	Ord.No.
S U2Z100 100m	75449

Flat Cables

AWG 28 x F



Flat color cable, tinned, PVC isolation, high flexibility. Suitable for self-cutting connectors.
Wire area 0,087 mm²
RM 1,27 mm
Working voltage max. 300V
Working temperature -20°C to 105°C
30,5m reel.

Part No.	Description
AWG 28-10 F 30,5m	Cable flat colour 30,5m 10-wire
AWG 28-20 F 30,5m	Cable flat colour 30,5m 20-wire
AWG 28-34 F I 30,5m	Cable flat colour 30,5m 34-wire
AWG 28-40 F I 30,5m	Cable flat colour 30,5m 40-wire

Part No.	Ord.No.
S AWG 28-10 F 30,5m	18512
S AWG 28-20 F 30,5m	18515
S AWG 28-34 F I 30,5m	18518
S AWG 28-40 F I 30,5m	18519

AWG 28 x G



Flat grey cable, suitable for self-cutting connectors.
Wire area 0,087 mm²
RM 1,27 mm
Max. voltage 300V
Working temperature -40°C to 105°C
30,5m reel.

Part No.	Description
AWG 28-10 G I 30,5m	Cable flat grey 30,5m 10-wire
AWG 28-14 G I 30,5m	Cable flat grey 30,5m 14-wire
AWG 28-16 G I 30,5m	Cable flat grey 30,5m 16-wire
AWG 28-20 G I 30,5m	Cable flat grey 30,5m 20-wire
AWG 28-25 G I 30,5m	Cable flat grey 30,5m 25-wire
AWG 28-26 G I 30,5m	Cable flat grey 30,5m 26-wire
AWG 28-34 G I 30,5m	Cable flat grey 30,5m 34-wire
AWG 28-40 G I 30,5m	Cable flat grey 30,5m 40-wire
AWG 28-50 G I 30,5m	Cable flat grey 30,5m 50-wire
AWG 28-60 G I 30,5m	Cable flat grey 30,5m 60-wire
AMP 0-0971111-4	Cable Flat Grey AWG28/34-wire 152m

Part No.	Ord.No.
S AWG 28-10 G I 30,5m	18498
S AWG 28-14 G I 30,5m	18499
S AWG 28-16 G I 30,5m	18501
S AWG 28-20 G I 30,5m	18502
S AWG 28-25 G I 30,5m	18504
S AWG 28-26 G I 30,5m	18505
S AWG 28-34 G I 30,5m	18506
S AWG 28-40 G I 30,5m	18508
S AWG 28-50 G I 30,5m	18509
S AWG 28-60 G I 30,5m	18510
S AMP 0-0971111-4 152m	53782

FBL Series

Flat color cables for universal use. 10m reel.



Part No.	Description
FBL-A10/0,25 10m	Cable flat colour 10x0,25mm ² RM1,39mm
FBL-A10/0,50 10m	Cable flat colour 10x0,5mm ² RM1,78mm
FBL-X10/0,14 10m	Cable flat colour 10x0,14mm ² RM1,27mm

Part No.	Ord.No.
S FBL-A10/0,25 10m	51005
S FBL-A10/0,50 10m	51006
S FBL-X10/0,14 10m	44614