WIHA SoftFinish Electric

Applications on live equipment are subject to very special requirements. The focus is on absolute user safety and Wiha demonstrates this with a wealth of details.



The high quality blade insulation ismoulded directly onto the blade and therefore guarantees safety whenworking on live equipment up to 1500VDCor 1000VAC.

To maintain this safety, each screwdriver of the SoftFinish®electric series is individually tested in a waterbath at 10000 Volts according to IEC60900:2004.

The roll-off protection and the special handle geometry offer optimum handling and electrical safety, even in critical applications.



Easily and safely, the high-quality blade insulation protects the user when working with live components. The insulation is moulded directly onto the blade and cannot be detached from the handle.

Slotted Insulated Screwdrivers

320N Series - SoftFinish Electric Slotted Screwdrivers



Insulation 1.000 V AC, VDE-tested and with GS mark.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish. Insulation moulded directly onto blade. Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off pro-

8.5 a 155

tection. Standards:DIN 7437, DIN 5264, ISO 2380. Manufactured acc. to IEC

60900:2004. Application: For all work on or around electrical components up to 1000 V AC

Application. For all work on or around electrical components up to 1000 v AC						
Part No.	\oplus	\ominus ;			— +	
320N 2,5x0,4x75	2,5	0,4	75	179	23	
320N 3,0x0,5x100	3,0	0,5	100	204	23	
320N 4,0x0,8x100	4,0	0,8	100	211	30	
320N 5,5x1,0x125	5,5	1,0	125	243	36	
Destable		0.111				
Part No.		Ord.No.				

S	320N 2,5x0,4x75	63639
s	320N 3,0x0,5x100	63723
s	320N 4,0x0,8x100	63724
s	320N 5.5x1.0x125	63725

Phillips Insulated Screwdrivers

321N Series - SoftFinish electric Phillips Screwdrivers



Insulation 1.000 V AC, VDE-tested and with GS mark.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish. Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards:DIN 7438, ISO 8764. Manufactured acc. to IEC 60900:2004. Application:For all work on or around electrical components up to 1000 V AC

\oplus	•1			—÷
PH0	-	60	164	23
PH1	-	80	191	30
PH2	-	100	218	36
	Ord No			
	63726			
	63732			
	63734			
	PH0 PH1	PH0 - PH1 - PH2 - Ord.No. 63726 63732	PH0 - 60 PH1 - 80 PH2 - 100 Ord.No. 63726 63732	PH0 - 60 164 PH1 - 80 191 PH2 - 100 218 Ord.No. 63726 - 63732 -

POZIDRIV Insulated Screwdrivers

324 Series - SoftFinish Electric Pozidriv Screwdrivers





Insulation 1.000 V AC, VDE-tested and with GS mark.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish. Insulation moulded directly onto blade. Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off pro-

tection. Standards:DIN 7438, ISO 8764. Manufactured acc. to IEC 60900:2004 Application:For all work on or around electrical components up to 1000 V AC

Part No.	+			—÷
324 PZ0x60	PZ0	60	164	23
324 PZ1x80	PZ1	80	191	30
324 PZ2x100	PZ2	100	218	36
Part No.	Ord.No.			
S 324 PZ0x60	63735			
S 324 PZ1x80	63736			
S 324 PZ2x100	63737			

Hex Nut Screwdrivers

322 Series - SoftFinish Electric Hex Nut Driver

SW 8,0 + 125	 0	4	liha

Insulation 1.000 V AC, VDE-tested and with GS mark.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish. Insulation moulded directly onto blade. Deep drawn socket.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards:DIN 3125. Manufactured acc. to IEC 60900:2004. Application:For external hex screws and hex nuts.

Part No.	0		===	—÷	-
322 SW5x125	5	125	236	30	-
322 SW5,5x125	5,5	125	236	30	11,2
322 SW8x125	8	125	243	36	15,2
Part No.		Ord.No.			
S 322 SW5x125		63738			
S 322 SW5,5x125		63739			
S 322 SW8x125		63740			

1000 V AC Screwdriver Sets

320N K6 Series-SoftFinish Electric Slotted/ Phillips Screwdriver Set, 6 pcs



Insulation 1.000 V AC, VDE-tested and with GS mark.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish. Insulation moulded directly onto blade.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards:Manufactured acc. to IEC 60900:2004. Application:For all work on or around electrical components up to 1000 V AC

\oplus	320N	3,0x100	4,0x100	5,5x125	6,5x150
$\overline{\oplus}$	321N	PH1x80	PH2x100	-	-
Part No.	C	rd.No.			
S 320N K6	6	3746			

