

## ERSADUR Soldering and Desoldering Tips 832 Series

Pb free




Conical



Chisel



PLCC blade



PowerWell

Suitable for:


- ANALOG 60/60A
- ANALOG 80/80A
- DIGITAL 2000A
- DIGITAL 80A
- MICRO-CON
- MS 6000
- MS 8000
- RDS 80

Part No.	Ord.No.	Description
S 832 UD LF	40170	Conical 0,4x55mm
S 832 SD LF	40172	Conical 0,8x55mm
S 832 BD LF	40174	Conical 1,0x46mm
S 832 YD LF	47675	Chisel 1,6x46mm
S 832 CD LF	40176	Chisel 2,2x46mm
S 832 KD LF	2695	Chisel 2,2x55mm
S 832 ED LF	40177	Chisel 3,2x46mm
S 832 AD	7309	PLCC blade 1,5mm
S 832 PW LF	40866	PowerWell with concave portion 4x40mm


## ERSA i-Tip Soldering Tips

Pb free


Specially plated with the new ERSADUR-LF galvanic process lasting 2 to 3 times longer than standard tips. Suitable for the i-Tool




0102ADLF



0102CDLF



0102PDLF



0102WDLF

Part No.	Ord.No.	Description
O 0102ADLF20	69322	Angled face, L= 2,0mm
O 0102CDLF12	66241	Chisel 0,6x1,2mm
O 0102CDLF16	60883	Chisel 0,6x1,6mm
O 0102CDLF20	60884	Chisel 0,8x2,0mm
O 0102CDLF32	66242	Chisel 1,0x3,2mm
O 0102PDLF02	63911	Pencil 0,2mm
O 0102PDLF04	60880	Pencil 0,4mm
O 0102PDLF04L	69323	Pencil 0,4mm
O 0102PDLF07	60881	Pencil 0,7mm
O 0102PDLF10	60882	Pencil 1,0mm
O 0102WDLF16	67398	Solder well, L= 1,6mm
O 0102WDLF23	67399	Solder well, L= 2,3mm

## Gas Soldering Irons

ERSA



### Independent 75 Basic

The ergonomic, antistatic gas soldering iron with piezo ignition is ideal for service and maintenance work, especially if there is no power supply available! The continuously adjustable output of 15 - 75 W (compared with electrical soldering irons) allows maximum soldering tip temperatures of up to 580 °C. The Independent is powered by ordinary butane as used in gas lighters. Operating time per gas filling is about 60 min.

Technical Parameters	Independent 75 Basic
Power	15-75W
Temperature	500°C
Heating Time	approx. 30s to 185°C
Set contains	2x soldering tips, sponge, holder

Part No.	Ord.No.
O INDEPENDENT 75 BASIC	39329

### Soldering Tips for INDEPENDENT

#### G 052 BN



#### G 072 CN



Part No.	Ord.No.	Description
S G 052 BN	44556	0,5mm Conical for INDEPENDENT 50
S G 072 CN	47982	1,0mm Chisel for INDEPENDENT 75

## Accessories

ERSA



### 003B

Replacement Solder Tip Cleaning Sponge for ERSADUR Stations  
Dimensions: 55x55x13mm.

Part No.	Ord.No.
S 003B Sponge	5942



### VAC X

Antistatic standard solder sucker. The feature of the solder sucker ERSADUR VAC X is the high pumping performance and the ergonomic shape. The antistatic construction allows carefree desoldering of electrostatically irritable assemblies. The long, slim desoldering tip also allows work on closely assembled boards. The special construction allows easy cleaning of the pump and exchange of the desoldering tip.



### VAC X2/SB

Spare desoldering teflon nozzle for VAC X.

Part No.	Ord.No.
S VAC X	48333
S VAC X2/SB	48334