

Button Cells Battery Holders

BH500

KEYSTONE



SN 2032



SN 2430



Part No.	Ord.No.	Description
S BH 500	2283	CR 1216, 1220, 1225(12mm)
S SN 2032	2643	CR 2032 (20mm) RM20
S SN 2430	3639	CR 2430 (24,5mm) RM20

Battery Clips

KEYSTONE

BCL82PC



BCL92PC



BCL595PC



BCL628PC



Part No.	Ord.No.	Description	1+	10+	25+
S BCL 82 PC	5687	AAA/N			
S BCL 92 PC	10747	AAA/AA			
S BCL 595 PC	7943	AAA/AA +pole			
S BCL 628 PC	7944	AAA/AA - pole			

BCL204

BCL209



BCL228




Part No.	Ord.No.	Description
O BCL 204	55732	AAAA/AAA/N/12V - pole
S BCL 209	49106	AAA/AA - pole
S BCL 228	55734	AAAA/AAA/N/12V + pole

BCL210

BCL238

BCL290



Part No.	Ord.No.	Description
O BCL 210	49107	2xAAA/AA - pole
O BCL 238	55737	2xAAA/AA + pole
O BCL 290	55738	2xAAA/AA +/- pole



Chargers

Battery Chargers with DV Detection



Chargers with ΔV detection could effectively prevent overcharge of batteries by switching the charge cycle from fast mode to trickle mode when the charger detected the abrupt change of voltage and other parameters. Since the chargers with ΔV detection usually have a well-designed protection circuit, the Charging Current of this kind of chargers is around 0,25C-1C (C=battery's capacity). REFRESH feature allows to regenerate battery's capacity, which is reduced due to memory effect. Plug-in versions have European fork directly on the charger, desktop versions are equipped with a solid flex.



MW 8168 GS

Intercept 5 Hours Battery Charger w/ DV Control, Discharge Function & 1500mAh batteries
2/4 switch
For AA & AAA Ni-Cd/Ni-MH batteries
Plug-in

ΔV

Technical Parameters	MW 8168 GS
Input Voltage	230 VAC
Battery Type	NiCd/NiMH
Battery Size	AAA, AA
Charging Current - fast charge	500mA (AA), 300mA (AAA)
Charging Current - trickle charge	50mA (AA), 30mA (AAA)
Discharge function	yes
Input Method	plug-in
Dimension	119x71x83mm

Part No.	Ord.No.
S MW 8168 GS	52015



MW 1268

Intercept-Rapid Battery Charger w/ DV control, USB input, discharge & memory refresh function
2/4 switch
For AA & AAA Ni-Cd/Ni-MH batteries

Accessories:
car adaptor MWCP1
AC/DC adaptor MW1205GS

ΔV

USB

Technical Parameters	MW 1268
Input Voltage	AC 100-230V, DC 12-13.8V, 5V(USB)
Battery Type	NiCd/NiMH
Battery Size	AAA, AA
Charging Current - fast charge	800mA (AA), 300mA (AAA)
Charging Current - trickle charge	80mA (AA), 30mA (AAA)
Discharge function	yes
Input Method	AC & DC Input
Dimension	119x71x83mm

Part No.	Ord.No.
S MW 1268	49291



MW L 2111(1)

Aluminum battery charger LCD with backlight
4 channels

Accessories:
car adaptor MWCP1
AC/DC adaptor MW1205GS

ΔV

LCD

Technical Parameters	MW L2111(1)
Input Voltage	AC 230V
Battery Type	Ni-Cd/Ni-MH
Battery Size	AAA, AA
Charging Current - fast charge	800mA (AA), 300mA (AAA)
Charging Current - trickle charge	80mA (AA), 30mA (AAA)
Discharge function	no
Input Method	Desktop
Dimension	124.5 x 72 x 30mm

Part No.	Ord.No.
S MW L 2111(1)	70393