

MW 2P200, MW 2P300



Technical Parameters	MW 2P200	MW 2P300
Input Voltage	200-240 VAC	
Output Voltage	100-120 VAC	
Rated Power	200 W	300 W
Dimensions [mm]	198x136x101	
Note	Desktop	

Part No.	Ord.No.
S MW 2P200	49286
S MW 2P300	49287

MW200, MW500, MW1000



Technical Parameters	MW200	MW500	MW1000
Input Voltage	220-240 VAC		
Output Voltage	110-120 VAC		
Rated Power	200W	500W	1000W
Dimensions [mm]	130x90x80	163x105x95	215x118x155
Note	Desktop 1xUS-socket	Desktop 2xUS-socket	Desktop

Part No.	Ord.No.
O MW200	44962
S MW500	48070
S MW1000	47258

12(24) VDC/115VAC Voltage Converters

GP-12-xx, GP-24-1xx Series



Technical Parameters	GP-12-150	GP-12-300
Input Voltage	10-14 VDC	10-14 VDC
Output Voltage	230 VAC	230 VAC
Rated load	150/450W	300/1000 W
Dimensions [mm]	165x86x49	165x86x49
Note	softstart	softstart

Technical Parameters	GP-24-150	GP-24-300	GP-24-1000
Input Voltage	24 VDC	24 VDC	24 VDC
Output Voltage	230 VAC	230 VAC	230 VAC
Rated load	150/450W	300/1000 W	1000/2500
Dimensions [mm]	165x86x49	165x86x49	344x122x79
Note	softstart	softstart	softstart

Part No.	Ord.No.
S GP-12-150	59957
S GP-12-300	58134
S GP-24-150	60531
S GP-24-300	58135

G-12-300SINUS



SP 600-012



Technical Parameters	G-12-300SINUS	SP 600-012
Input Voltage	10-14 VDC	10 - 15 VDC
Output Voltage	230 VAC	230 VAC
Rated Power	300/500 W	600/1500W
Dimensions	205x242x82mm	200x173x65mm
Note	Output Voltage has pure sine wave form	modified sine wave

Part No.	Ord.No.
O G-12-300SINUS	58129
S SP 600-012	72916

SW-x-12, SW-x-24 series



Technical Parameters	SW-150-12	SW-300-12	SW-300-24
Input Voltage	11-15 VDC	11-15 VDC	22-30 VDC
Output Voltage	230 VAC	230 VAC	230 VAC
Rated Power	150W	300 W	300 W
Dimension	120x245x70mm	240x245x70mm	240x245x70mm
Note	sinusoidal output	sinusoidal output	sinusoidal output

Technical Parameters	SW-600-12	SW-1200-12	SW-1200-24
Input Voltage	11-15 VDC	11-15 VDC	22-30 VDC
Output Voltage	230 VAC	230 VAC	230 VAC
Rated Power	600W	1200 W	1200 W
Dimension	340x245x70mm	390x245x70mm	390x245x70mm
Note	sinusoidal output	sinusoidal output	sinusoidal output

Technical Parameters	SW-2000-12	SW-2000-24
Input Voltage	11-15 VDC	22-30 VDC
Output Voltage	230 VAC	230 VAC
Rated Power	2000 W	2000 W
Dimension	455x245x70mm	455x245x70mm
Note	sinusoidal output	sinusoidal output

Part No.	Ord.No.
O SW-150-12	65066
O SW-300-12	65067
O SW-300-24	69279
S SW-600-12	65069
S SW-1200-12	65070
O SW-1200-24	68575
O SW-2000-12	65071
S SW-2000-24	68634