

Headers

to ASP046

- Type 219** page 134
- Type 220** page 135
- Type 179** page 135
- Type 286** page 136
- Type 290** page 137
- Type 229** page 138
- Type 230** page 139
- Type 178** page 139
- Type 288** page 140
- Type 292** page 141

Accessories

for ASP046

(only in combination with headers type 178, 179, 219, 220, 229 and 230)

coding set

700025 page 168

Description ASP046

Spring clamp terminal block, pluggable, centerline 5.08 mm / 0.200 inches, wire entry parallel to plug direction


Technical Data ASP046

UL V / A / AWG 300 / 8 / 28 - 16

0.08 - 1 mm² 250 V / 4 kV / 3 / 10 A
 Insulation co-ordination according to IEC 664-1
 Clearance and creepage distance ≥ 4 mm

- Wire diameter single wire 0.3 - 1.3 mm
- Wire strip length 4 mm / 0.157 in.
- Contact resistance from the termination point via header to the pc board ≤ 4 mΩ per pole
- Pole size 2 to 24
- Color (standard) black
- Color (optional) green

Dimensions in mm 1 mm = 0.0394 in.



$L = (\text{pole size} - 1) \times \text{centerline} + 5 \text{ mm} / 0.197 \text{ in.}$

Color Options

Suffix	Color
02	black (standard)
06	green

Please order terminal block and header in the same color.

Part numbers (P/N)

Complete the part number by adding the pole size..

ASP046

centerline 5.08 mm / 0.200 inches

P/N ASP046

	02	03	04	05	06	07	08
09	10	11	12	13	14	15	16
17	18	19	20	21	22	23	24

ASP04A

centerline 10.16 mm / 0.400 inches

P/N ASP04A

	02	03	04	05	06	07	08
09	10	11	12				

* approval pending

- Standard pole sizes**
- Available on demand. Minimum order quantity 5000 poles per item.**